

## P/N 4002-3SW

## **Description**

total panel thickness 0.081" - 0.11", corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### 11420016-3

SKU / Model: 40023SW

Minimum Qty (MOQ):

NSN: 5325-00-085-4126

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 4002-3SW Specifications

Head Length:	0.850 Inches Minimum And 0.890 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.483 Inches Minimum And 0.498 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.257 Inches Nominal
Material Accommodated Thickness:	0.111 Inches Minimum And 0.140 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Head
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

# **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-3SW">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-3SW</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.