

Description

total panel thickness 0.081" - 0.11", corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[11420016-3](#)

| | |
|-------------------------|--|
| SKU / Model: | 40023SW |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5325-00-085-4126 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



P/N 4002-3SW Specifications

| | |
|--|--|
| Head Length: | 0.850 Inches Minimum And 0.890 Inches Maximum |
| Turnlock Stud Head Style: | Flat Countersunk Wing |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.483 Inches Minimum And 0.498 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.257 Inches Nominal |
| Material Accommodated Thickness: | 0.111 Inches Minimum And 0.140 Inches Maximum |
| Material: | Steel Comp 302 Ejector Spring |
| Material: | Steel Comp 302 Stud |
| Material: | Steel Comp 302 Head |
| Material: | Steel Comp 302 Pin |
| Material: | Steel Comp 305 Eyelet |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-3SW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.