

Description

Cadmium plated steel, slotted recess, total panel thickness: 0.111" - 0.140

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[1142000-4](#)

SKU / Model:	40024
Minimum Qty (MOQ):	10
NSN:	5325-00-290-8028
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N 4002-4 Specifications

Diameter:	0.380 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.513 Inches Minimum And 0.523 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.257 Inches Nominal
Material Accommodated Thickness:	0.141 Inches Minimum And 0.170 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.098 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.