

Description

Thickness 0.111" - 0.140", corrosion resistant steel, quarter turn, 4002 series

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[1142016-4](#)

SKU / Model:	40024SW
Minimum Qty (MOQ):	1
NSN:	5325-00-015-7952
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 4002-4SW Specifications

Head Length:	0.880 Inches Minimum And 0.890 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.730 Inches Minimum And 0.770 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.257 Inches Nominal
Material Accommodated Thickness:	0.141 Inches Minimum And 0.170 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud Or Steel Corrosion Resisting Stud
Material:	Steel Comp 302 Head
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Pin
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Stud Or Type 384,cagec 71321 Mfr Ref Single Material Response Stud
Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Eyelet
Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Head
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-4SW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.