

**Description**

cadmium plated steel - slotted recess, total panel thickness: 0.141"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	40025
Minimum Qty (MOQ):	10
NSN:	5325-00-290-8235
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

## P/N 4002-5 Specifications

<b>Diameter:</b>	0.377 Inches Minimum And 0.384 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.543 Inches Minimum And 0.583 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.292 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.171 Inches Minimum And 0.200 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Ejector Spring
<b>Material:</b>	Steel Eyelet
<b>Material:</b>	Steel Pin
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Ejector Spring
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Pin
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 2 Fed Spec All Treatment Responses Overall

## How to Order

Order this camloc, 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.