

## P/N 4002-6SW

### **Description**

4002-6SW Turnlock Fastener Stud Assembly

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 40026SW

Minimum Qty (MOQ): 2

NSN: 5325-00-584-1360

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









<sup>\*</sup> See page 2 for technical characteristics

# P/N 4002-6SW Specifications

Head Length:	0.850 Inches Minimum And 0.890 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.573 Inches Minimum And 0.588 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.201 Inches Minimum And 0.230 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Head
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

# **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-6SW">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-6SW</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.