

Description

1/4 turn stud 4002-6W flat countersunk wing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[1142007-6](#)

| | |
|-------------------------|--|
| SKU / Model: | 40026W |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-534-0373 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 4002-6W Specifications

| | |
|--|--|
| Head Length: | 0.850 Inches Minimum And 0.890 Inches Maximum |
| Turnlock Stud Head Style: | Flat Countersunk Wing |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.573 Inches Minimum And 0.588 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.201 Inches Minimum And 0.230 Inches Maximum |
| Material: | Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Comp 1112 Eyelet |
| Material: | Steel Comp 1009 Head |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Pin |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Ejector Spring |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-6W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.