# P/N 4002-6W

## **Description**

1/4 turn stud 4002-6W flat countersunk wing

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

### 1142007-6

SKU / Model: 40026W

Minimum Qty (MOQ): 5

NSN: 5325-00-534-0373

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









# P/N 4002-6W Specifications

Head Length:	0.850 Inches Minimum And 0.890 Inches Maximum
neau Lengtin	0.050 Inches Millimani And 0.050 inches Maximani
Turnlock Stud Head Style:	Flat Countersunk Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.573 Inches Minimum And 0.588 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.201 Inches Minimum And 0.230 Inches Maximum
Material:	Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Comp 1112 Eyelet
Material:	Steel Comp 1009 Head
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall

## **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-6W">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-6W</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.