



# MILITARY ★ FASTENERS

Military-Fasteners.com

## P/N 4002-8SW

### Description

total panel thickness 0.231" - 0.26", winged, corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### Additional Information

SKU / Model:	40028SW
Minimum Qty (MOQ):	2
NSN:	5325-00-825-2201
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 4002-8SW Specifications

<b>Head Length:</b>	0.850 Inches Minimum And 0.890 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Flat Countersunk Wing
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.633 Inches Minimum And 0.648 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.382 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.261 Inches Minimum And 0.290 Inches Maximum
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 302 Stud
<b>Material:</b>	Steel Comp 302 Head
<b>Material:</b>	Steel Comp 302 Pin
<b>Material:</b>	Steel Comp 305 Eyelet
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-8SW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.