

Description

Diameter: 3/8", steel ejector spring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | 40029 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-171-5789 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 4002-9 Specifications

| | |
|--|--|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Securing Device Type: | Spring |
| Turnlock Stud Head Style: | Flat Countersunk |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.663 Inches Minimum And 0.673 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.412 Inches Nominal |
| Material Accommodated Thickness: | 0.291 Inches Minimum And 0.320 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Comp 1112 Eyelet |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Pin |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Ejector Spring |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-41,ty 2 Cl 2 Fed Spec All Treatment Responses Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.