

Description

panel thickness 0.074", maximum dimpled panel thickness 0.064", requires retaining ring, flush head, cadmium plated steel,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1142900-1](#) [4002G](#)

SKU / Model:	4002G
Minimum Qty (MOQ):	10
NSN:	5325-00-449-2797
ECCN:	EAR99
National Motor Freight:	094533, Eyelets Or Eyelet Hooks Noi



* See page 2 for technical characteristics

P/N 4002-G Specifications

Turnlock Eyelet Style:	Eyelet
Eyelet Height:	0.183 Inches Minimum And 0.191 Inches Maximum
Distance Between Flanges:	0.124 Inches Minimum And 0.132 Inches Maximum
Smallest Outside Diameter:	0.467 Inches Minimum And 0.473 Inches Maximum
Largest Outside Diameter:	0.617 Inches Minimum And 0.625 Inches Maximum
Eyelet Inside Diameter:	0.344 Inches Nominal
Material:	Steel Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Astm B633,ty 3 Assn Std Single Treatment Response Overall

How to Order

Order this turnlock fastener eyelet from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+eyelets/4002-G> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.