

**Description**

flush head - corrosion resistant steel - maximum standard panel thickness 0.074", maximum dimpled panel thickness 0.064", requires retaining ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	4002GS
Minimum Qty (MOQ):	10
NSN:	5325-00-584-1270
National Motor Freight:	094533, Eyelets Or Eyelet Hooks Noi

NO IMAGE  
AVAILABLE

## P/N 4002-GS Specifications

<b>Turnlock Eyelet Style:</b>	Eyelet
<b>Eyelet Height:</b>	0.183 Inches Minimum And 0.191 Inches Maximum
<b>Distance Between Flanges:</b>	0.124 Inches Minimum And 0.132 Inches Maximum
<b>Smallest Outside Diameter:</b>	0.467 Inches Minimum And 0.473 Inches Maximum
<b>Largest Outside Diameter:</b>	0.617 Inches Minimum And 0.625 Inches Maximum
<b>Eyelet Inside Diameter:</b>	0.351 Inches Minimum And 0.357 Inches Maximum
<b>Material:</b>	Steel Overall

## How to Order

Order this turnlock fastener eyelet from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+eyelets/4002-GS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.