

Description

Fastener Length: 33/64", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	4020685
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-392-1621
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 4020685 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.300 Inches Minimum And 0.385 Inches Maximum
Fastener Length:	0.510 Inches Minimum And 0.530 Inches Maximum
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Shoulder Diameter:	0.2188 Inches Minimum First Shoulder And 0.2193 Inches Maximum First Shoulder
Shoulder Length:	0.145 Inches Minimum First Shoulder And 0.165 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/4020685> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.