

Description

Diameter: 3/8", steel overall

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	40S457
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-498-0818
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 40S45-7 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.705 Inches Nominal
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.352 Inches Nominal
Material Accommodated Thickness:	0.231 Inches Minimum And 0.260 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.102 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S45-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.