

**Description**

total panel thickness 0.291" - 0.320", cadmium plated steel philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1142005-10](#)

SKU / Model:	40S510
Minimum Qty (MOQ):	10
NSN:	5325-01-124-1299
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 40S5-10 Specifications

<b>Diameter:</b>	0.377 Inches Minimum And 0.384 Inches Maximum
<b>Securing Device Type:</b>	Spring
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.693 Inches Minimum And 0.703 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.432 Inches Minimum And 0.452 Inches Maximum
<b>Material Accommodated Thickness:</b>	0.321 Inches Minimum And 0.350 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Material:</b>	Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Eyelet
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Ejector Spring
<b>Material:</b>	Steel Pin
<b>Material Document And Classification:</b>	Astm A108 Assn Std Single Material Response Eyelet
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Ejector Spring
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Pin
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.