

**Description**

cadmium plated steel philips recess - total panel thickness 0.351" - 0.380"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | 40S512                                 |
| Minimum Qty (MOQ):      | 10                                     |
| NSN:                    | 5325-00-414-4738                       |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE  
AVAILABLE

## P/N 40S5-12 Specifications

|  |   |
|--|---|
| <b>Diameter:</b>   | 0.377 Inches Minimum And 0.384 Inches Maximum                 |
| <b>Securing Device Type:</b>   | Washer  |
| <b>Turnlock Stud Head Style:</b>   | Stud Head   |
| <b>Stud Assembly Style:</b>  | Stud Assembly   |
| <b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b> | 0.753 Inches Minimum And 0.763 Inches Maximum                 |
| <b>Eyelet Outside Diameter:</b>  | 0.341 Inches Minimum And 0.348 Inches Maximum                 |
| <b>Eyelet Length:</b>  | 0.502 Inches Nominal  |
| <b>Material Accommodated Thickness:</b>                                  | 0.261 Inches Minimum And 0.410 Inches Maximum                 |
| <b>Drive Type:</b>   | Cross Recess  |
| <b>Stud Head Height:</b>   | 0.092 Inches Nominal  |
| <b>Material:</b>   | Steel Overall   |
| <b>Surface Treatment:</b>  | Cadmium Overall And Chromate Overall                          |
| <b>Surface Treatment Document And Classification:</b>                    | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.