

**Description**

total panel thickness 0.411" - 0.440", cadmium plated steel, philips recess, 40S5 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1142005-14](#)

SKU / Model:	40S514
Minimum Qty (MOQ):	5
NSN:	5325-00-840-6030
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 40S5-14 Specifications

<b>Diameter:</b>	0.377 Inches Minimum And 0.384 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Stud Head
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.813 Inches Minimum And 0.823 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.562 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.441 Inches Minimum And 0.470 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Stud Head Height:</b>	0.092 Inches Minimum And 0.112 Inches Maximum
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.