

# P/N 40S5-14

## **Description**

total panel thickness 0.411" - 0.440", cadmium plated steel, philips recess, 40S5 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### 1142005-14

SKU / Model: 40S514

Minimum Qty (MOQ): 5

NSN: 5325-00-840-6030

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









# P/N 40S5-14 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.813 Inches Minimum And 0.823 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.562 Inches Nominal
Material Accommodated Thickness:	0.441 Inches Minimum And 0.470 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.092 Inches Minimum And 0.112 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

## **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-14">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-14">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-14</a>