

**Description**

total panel thickness 0.441" - 0.470", cadmium plated steel, philips recess, 40S5 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1142005-15](#)

SKU / Model:	40S515
Minimum Qty (MOQ):	5
NSN:	5325-01-314-4973
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	179735, Studs Vehicle Tire Roadway Surface



\* See page 2 for technical characteristics

# P/N 40S5-15 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Material Accommodated Thickness:	0.471 Inches Minimum And 0.500 Inches Maximum
Drive Type:	Cross Recess
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.