

## Description

Diameter: 3/8", steel comp eyelet, 40S5 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[1142005-16](#)

SKU / Model:	40S516
Minimum Qty (MOQ):	10
NSN:	5325-00-078-7560
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 40S5-16 Specifications

<b>Diameter:</b>	0.380 Inches Nominal
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.843 Inches Minimum And 0.873 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.257 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.501 Inches Minimum And 0.530 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 302 Stud
<b>Material:</b>	Steel Comp 302 Pin
<b>Material:</b>	Steel Comp 305 Eyelet
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.