

Description

total panel thickness 0.171" - 0.20", cadmium plated steel, philips recess, camloc, 40S5 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1142005-6](#)

| | |
|-------------------------|--|
| SKU / Model: | 40S56 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-883-0945 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 40S5-6 Specifications

| | |
|--|---|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.573 Inches Minimum And 0.583 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.081 Inches Minimum And 0.230 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.092 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.