

**Description**

total panel thickness 0.171" - 0.20", cadmium plated steel, philips recess, camloc, 40S5 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1142005-6](#)

|                         |  |
|-------------------------|--|
| SKU / Model:            | 40S56                                  |
| Minimum Qty (MOQ):      | 10                                     |
| NSN:                    | 5325-00-883-0945                       |
| ECCN:                   | EAR99                                  |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



\* See page 2 for technical characteristics

## P/N 40S5-6 Specifications

|  |   |
|--|---|
| <b>Diameter:</b>   | 0.377 Inches Minimum And 0.384 Inches Maximum |
| <b>Turnlock Stud Head Style:</b>   | Stud Head                                     |
| <b>Stud Assembly Style:</b>  | Stud Assembly                                 |
| <b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b> | 0.573 Inches Minimum And 0.583 Inches Maximum |
| <b>Eyelet Outside Diameter:</b>  | 0.341 Inches Minimum And 0.348 Inches Maximum |
| <b>Eyelet Length:</b>  | 0.322 Inches Nominal                          |
| <b>Material Accommodated Thickness:</b>                                  | 0.081 Inches Minimum And 0.230 Inches Maximum |
| <b>Drive Type:</b>   | Cross Recess                                  |
| <b>Stud Head Height:</b>   | 0.092 Inches Nominal                          |
| <b>Material:</b>   | Steel Overall                                 |
| <b>Surface Treatment:</b>  | Cadmium Overall And Chromate Overall          |

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.