

Description

total panel thickness 0.201" - 0.230", cadmium plated steel, philips recess, 40S5 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1142005-7](#)

SKU / Model:	40S57
Minimum Qty (MOQ):	5
NSN:	5325-00-369-2716
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 40S5-7 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.603 Inches Minimum And 0.613 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.352 Inches Nominal
Material Accommodated Thickness:	0.231 Inches Minimum And 0.260 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.377 Inches Minimum And 0.384 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.