

Description

total panel thickness 0.231" - 0.260", cadmium plated steel philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1142005-8](#)

SKU / Model:	40S58
Minimum Qty (MOQ):	10
NSN:	5325-00-799-1019
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 40S5-8 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.633 Inches Minimum And 0.643 Inches Maximum
Eyelet Outside Diameter:	0.412 Inches Minimum And 0.427 Inches Maximum
Eyelet Length:	0.382 Inches Nominal
Material Accommodated Thickness:	0.261 Inches Minimum And 0.290 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.082 Inches Minimum And 0.102 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/40S5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.