

## P/N 42FLW524

## **Description**

Thread Size: 1/4", Head Width: 3/8", locknut, 42FLW series nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 42FLW524

Minimum Qty (MOQ): 5

NSN: 5310-00-811-8050

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# **P/N 42FLW524 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.547 Inches Maximum
Lubrication:	Soluble Lubricant
Overall Height:	0.363 Inches Maximum
Nut Style:	Double Hexagon
Washer Thickness:	0.044 Inches Minimum
Width Across Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	34.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Steel Comp 8630 Overall Or Steel Comp 4037 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6280 Assn Std 1st Material Response Overall Or Ams6300 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this self-locking extended washer nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/42FLW524">https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/42FLW524</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.