

P/N 42FLW820

Military-Fasteners.com

Description

Thread: 1/2-20, Thread Size: 1/2", Nut Height: 1/2", Head Width: 5/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

<u>42FLW-820</u>	
SKU / Model:	42FLW820
Minimum Qty (MOQ):	5
NSN:	5310-01-357-7666
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N 42FLW820 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Free-running All Metal Design
Washer Outside Diameter:	0.813 Inches Minimum And 0.833 Inches Maximum
Overall Height:	0.539 Inches Minimum And 0.559 Inches Maximum
Nut Style:	Double Hexagon
Washer Thickness:	0.064 Inches Minimum And 0.084 Inches Maximum
Width Across Flats:	0.616 Inches Minimum And 0.627 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Hardness Rating:	34.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
Nominal Thread Size:	0.500 Inches
Criticality Code Justification:	Spcl
Special Features:	Used On (25500) 5002371-4 Wheel Assy's Of A-10 Mlg Acft
Material:	Steel Overall
Material Document And Classification:	Ms6280 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Special Test Features:	Must Be Qualified In Accordance With Applicable Oem Wheel Qualification Specification
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking extended washer nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/42FLW820</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.