

Description

Fastener Length: 55/64", Thread: 3-48, Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	481051
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-052-9814
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 48105-1 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Minimum And 0.240 Inches Maximum
Fastener Length:	0.830 Inches Minimum And 0.860 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.180 Inches Minimum And 0.200 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.099 Inches
Thread Quantity Per Inch:	48
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/48105-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.