

P/N 490144

Military-Fasteners.com

#### Description

Fastener Length: 7/8", Hole Diameter: 5/64", Thread: 1/4-C8, Thread Length: 51/64"

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	490144
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-971-7199
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N 490144 Specifications

Thread Direction:Right-handThread Length:0.794 Inches Minimum And 0.814 Inches MaximumFastenr Length:0.865 Inches Minimum And 0.885 Inches MaximumHead Style:Double Hexagon WholeHead Height:0.320 Inches Minimum And 0.340 Inches MaximumWidth Between Flats:0.320 Inches Minimum And 0.340 Inches MaximumWidth Between Flats:0.320 Inches Minimum And 0.340 Inches MaximumExtended Washer Diameter:0.320 Inches Minimum And 0.313 Inches MaximumHole Diameter:0.060 Inches Minimum And 0.070 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesHole Type:0.250 InchesHole Type:DrilledFeatures Provided:Finished HeadHardness Rating:0.00 Rockwell C Minimum Overall And 36.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Casnibit Overall	Thread Class:	За
Thread Length:.794 Inches Minimum And 0.814 Inches MaximumFastener Length:0.865 Inches Minimum And 0.885 Inches MaximumHead Style:Double Hexagon W/holeHead Style:0.320 Inches Minimum And 0.340 Inches MaximumWidth Between Flats:0.304 Inches Minimum And 0.313 Inches MaximumExtended Washer Diameter:0.428 Inches Minimum And 0.348 Inches MaximumExtended Washer Thickness:0.606 Inches Minimum And 0.048 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesHole Quantity:4Hole Quantity:1Hole Quantity Per Inch:C8Thread Quantity Per Inch:0.070 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:30.0 Microinches Baring Surface Of HeadSurface Finish:32.0 Microinches Baring Surface Of HeadMaterial Document And Classification:Kele Overall And Cadmium OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Mickel Overall And Cadmium Overall		
Fastener Length:0.865 Inches Minimum And 0.885 Inches MaximumHead Style:Double Hexagon W/holeHead Style:0.320 Inches Minimum And 0.340 Inches MaximumWidth Between Flats:0.304 Inches Minimum And 0.313 Inches MaximumExtended Washer Diameter:0.428 Inches Minimum And 0.448 Inches MaximumExtended Washer Thickness:0.600 Inches Minimum And 0.070 Inches MaximumHole Diameter:0.700 Inches Minimum And 0.070 Inches MaximumHole Quantity:0.500 Inches Minimum And 0.070 Inches MaximumHole Quantity:0.700 Inches NominalHole Quantity:0.700 Inches NominalHole Quantity:0.700 Inches NominalHole Countity:0.700 Inches NominalHole Countity:0.700 Inches NominalHole Countity:0.700 Inches NominalHorage Stating:0.100 Rockwell Countinum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:0.000 Inches Stating:Surface Flinish:3.00 Norches Bearing Surface Of HeadSurface Flinish:3.00 Norches Bearing Surface Of HeadMaterial:Steel Comp 601 OverallMaterial Document And Classification:Mickel Overall And Cadmium OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Mickel Overall And Cadmium Overall		
Head Style:Double Hexagon W/holeHead Height:0.320 Inches Minimu And 0.340 Inches MaximumWidth Between Flats:0.304 Inches Minimu And 0.313 Inches MaximumExtended Washer Diameter:0.428 Inches Minimu And 0.448 Inches MaximumExtended Washer Thickness:0.060 Inches Minimu And 0.070 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 Inches NominalHole Quantity:4Hole Quantity:10Hole Type:DrilledFreatures Provided:Finished HeadThread Quantity Per Inch:C8Hole Configuration Style:0.004 Increason Longitufial HoleSurface Finish:3.0.0 Nicroinches Bearing Surface Of HeadSurface Finish:6.3.0 Microinches Bearing Surface Of HeadMaterial Document And Classification:Micel Overall And Cadmium OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Micel Admium Overall	Thread Length:	0.794 Inches Minimum And 0.814 Inches Maximum
Head Height:0.320 Inches Minimum And 0.340 Inches MaximumWidth Between Flats:0.304 Inches Minimum And 0.313 Inches MaximumExtended Washer Diameter:0.428 Inches Minimum And 0.448 Inches MaximumExtended Washer Thickness:0.600 Inches Minimum And 0.070 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.270 Inches NominalHole Quantity:4Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:C8Hole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Nicroinches ThreadsSurface Finish:32.0 Microinches Rearing Surface Of HeadMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Non 6304 Assn Std All Treatment Responses Overall	Fastener Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Width Between Flats:0.304 Inches Minimum And 0.313 Inches MaximumExtended Washer Diameter:0.428 Inches Minimum And 0.448 Inches MaximumExtended Washer Thickness:0.060 Inches Minimum And 0.070 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesHole Quantity:4Hole Type:DilledFeatures Provided:Finished HeadThread Quantity Per Inch:68Hole Configuration Style:0.000 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:0.000 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches ThreadsSurface Finish:Stel Comp 601 OverallMaterial:Keel Overall And Classification:Surface Treatment:Nickel Overall And Casm Std Single Material Response OverallSurface Treatment:Nickel Overall And Casm Std All Treatment Responses Overall	Head Style:	Double Hexagon W/hole
Extended Washer Diameter:0.428 Inches Minimum And 0.448 Inches MaximumExtended Washer Thickness:0.600 Inches Minimum And 0.070 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesHole Quantity:4Hole Type:DilledFeatures Provided:Finished HeadThread Quantity Per Inch:C8Hole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:Stel Comp 601 OverallMaterial:Stel Comp 601 OverallMaterial:Mice Overall And Classification:Surface Treatment:Nickel Overall And Cassification:Surface Treatment:Nickel Overall And Classification:Surface Treatment:Nickel Overall And Classification:Surface Treatment:Nickel Overall And Classification:Surface Treatment:Nickel Overall And Classification:Surface Treatment:Nickel Overall And Classification:	Head Height:	0.320 Inches Minimum And 0.340 Inches Maximum
Extended Washer Thickness:0.060 Inches Minimum And 0.070 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:C8Hole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:3.0. Microinches Braing Surface Of HeadSurface Finish:Stel Comp 601 OverallMaterial:Stel Comp 601 OverallMaterial:Mics Style:Surface Treatment:Nickel Overall And Classification:Surface Treatment:Nickel Overall And Classification:Surface Treatment Document And Classification:Mics 2416 Assn Std All Treatment Responses Overall	Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Hole Diameter:0.070 Inches NominalNominal Thread Diameter:0.250 InchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:C8Hardness Rating:30.0 Rockwell C Minimun Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:Steel Comp 601 OverallMaterial Document And Classification:Mickel Overall And Cadmium OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Mickel Overall And Cadmium Overall	Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Nominal Thread Diameter:0.250 InchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:C8Hardness Rating:30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches Brearing Surface Of HeadMaterial:Stel Comp 601 OverallMaterial Document And Classification:Mickel Overall And Classification:Surface Treatment:Nickel Overall And Classification:Surface Treatment Document And Classification:Mic 2016 Assn Std All Treatment Responses Overall	Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Hole Quantity:4Hole Type:DrilledFeatures Provided:DrilledThread Quantity Per Inch:C8Hardness Rating:30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:Stel Comp 601 OverallMaterial Document And Classification:Mickel Overall And Classification:Surface Treatment:Mickel Overall And Classification:	Hole Diameter:	0.070 Inches Nominal
Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:C8Hardness Rating:30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Nominal Thread Diameter:	0.250 Inches
Features Provided:Finished HeadFread Quantity Per Inch:C8Hardness Rating:30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cassification:Surface Treatment Document And Classification:Mas 2416 Assn Std All Treatment Response Overall	Hole Quantity:	4
Thread Quantity Per Inch:C8Hardness Rating:30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Hole Type:	Drilled
Hardness Rating:30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHardness Rating:30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum OverallHole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Mas 2416 Assn Std All Treatment Responses Overall	Features Provided:	Finished Head
Hole Configuration Style:Double Hexagon Longitudinal HoleSurface Finish:32.0 Microinches ThreadsSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Material Ams 2416 Assn Std All Treatment Responses Overall	Thread Quantity Per Inch:	C8
Surface Finish:32.0 Microinches ThreadsSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Hardness Rating:	30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Surface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Steel Comp 601 OverallMaterial Document And Classification:Ams 6304 Assn Std Single Material Response OverallSurface Treatment:Nickel Overall And Cadmium OverallSurface Treatment Document And Classification:Ams 2416 Assn Std All Treatment Responses Overall	Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material Steel Comp 601 Overall   Material Document And Classification: Ams 6304 Assn Std Single Material Response Overall   Surface Treatment: Nickel Overall And Cadmium Overall   Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Ams 6304 Assn Std Single Material Response Overall   Surface Treatment: Nickel Overall And Cadmium Overall   Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Treatment: Nickel Overall And Cadmium Overall   Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Material:	Steel Comp 601 Overall
Surface Treatment Document And Classification: Ams 2416 Assn Std All Treatment Responses Overall	Material Document And Classification:	Ams 6304 Assn Std Single Material Response Overall
	Surface Treatment:	Nickel Overall And Cadmium Overall
Thread Series Designator: Unjf	Surface Treatment Document And Classification:	Ams 2416 Assn Std All Treatment Responses Overall
	Thread Series Designator:	Unjf

## How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/490144</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.