

Description

Fastener Length: 3/4", Thread: 5/16-24, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	493625
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-914-4250
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 493625 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	0.746 Inches Minimum And 0.786 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Nominal
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Shoulder Diameter:	0.490 Inches Nominal First Shoulder
Shoulder Diameter:	0.510 Inches Nominal Second Shoulder
Shoulder Length:	0.006 Inches Nominal First Shoulder
Shoulder Length:	0.026 Inches Nominal Second Shoulder
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Hardness Rating:	30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Shoulder Shape:	Round All Shoulders
Special Features:	3rd Shoulder Dia In. Nom 0.4336; 4th Shoulder Dia In. Nom 0.4356; 3rd Shoulder Lg In. Nom 0.257; 4th Shoulder Lg In. Nom 0.263
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5616 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/493625> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.