

Description

Fastener Length: 3/4", Thread: 5/16-24, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | 493625 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-914-4250 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 493625 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Minimum And 0.431 Inches Maximum |
| Fastener Length: | 0.746 Inches Minimum And 0.786 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.172 Inches Nominal |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Shoulder Diameter: | 0.490 Inches Nominal First Shoulder |
| Shoulder Diameter: | 0.510 Inches Nominal Second Shoulder |
| Shoulder Length: | 0.006 Inches Nominal First Shoulder |
| Shoulder Length: | 0.026 Inches Nominal Second Shoulder |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 30.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Shoulder Shape: | Round All Shoulders |
| Special Features: | 3rd Shoulder Dia In. Nom 0.4336; 4th Shoulder Dia In. Nom 0.4356; 3rd Shoulder Lg In. Nom 0.257; 4th Shoulder Lg In. Nom 0.263 |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams 5616 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/493625> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.