

## P/N 4M106-02014

### **Description**

Length: 23/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 4M10602014

Minimum Qty (MOQ): 5 EA

NSN: 3120-01-475-7833

National Motor Freight: 114800, Bearing,roller,thrust



# P/N 4M106-02014 Specifications

| Overall Length:                                | 0.7180 Inches Minimum And 0.7200 Inches Maximum  |
|--|--|
| Body Outside Diameter:                         | 0.1870 Inches Minimum And 0.1890 Inches Maximum  |
| Body Inside Diameter:                          | 0.1280 Inches Minimum And 0.1310 Inches Maximum  |
| Corner Shape:                                  | Square All Corners   |
| Material:                                      | Steel Comp 630 Overall   |
| Material Document And Classification:          | Ams 5643,cond H1025cxcygbushing Sleeve, Clamp Up Special Assn Std Single Material Response Overall |
| Surface Treatment:                             | Cadmium Overall  |
| Surface Treatment Document And Classification: | Qq-p-416, Type 2, Class 3 Fed Spec Single Treatment Response Overall                               |
| Style Designator:                              | 17c Solid, Plain, No Outside Flanges   |

## **How to Order**

Order this bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/4M106-02014">https://military-fasteners.com/bushings/sleeve+bushings/4M106-02014</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.