

P/N 4M106-05002

Description

Length: 9/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: 4M10605002

Minimum Qty (MOQ): 10 EA

NSN: 3120-00-447-7306

National Motor Freight: 114850, Bearing / Bushing O / T Ball / Roller I / S



^{*} See page 2 for technical characteristics

P/N 4M106-05002 Specifications

Overall Length:	0.2860 Inches Minimum And 0.2960 Inches Maximum
Body Outside Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Body Inside Diameter:	0.3125 Inches Minimum And 0.3130 Inches Maximum
Corner Shape:	Square All Corners
Surface Finish:	63.0 Microinches Left End Surface Of Body
Surface Finish:	63.0 Microinches Outside Diameter Surface Of Body
Surface Finish:	63.0 Microinches Right End Surface Of Body
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643,cond H1025 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges

How to Order

Order this bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/4M106-05002 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bushings/sleeve+bushings/4M106-05002 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bushings/sleeve+bushings/4M106-05002 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bushings/sleeve+bushings/4M106-05002 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bushings/4M106-05002 and selecting the property of the prope