

Description

Length: 1-31/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | 4M10608007 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 3120-00-442-8361 |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 4M106-08007 Specifications

| | |
|--|---|
| Overall Length: | 1.9730 Inches Minimum And 1.9780 Inches Maximum |
| Body Outside Diameter: | 0.6224 Inches Minimum And 0.6235 Inches Maximum |
| Body Inside Diameter: | 0.4995 Inches Minimum And 0.5005 Inches Maximum |
| Corner Shape: | Square All Corners |
| Special Features: | Dry Film Lubricant |
| Material: | Steel Comp 630 Overall |
| Material Document And Classification: | Ams 5643 Assn Std Single Material Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Test Data Document: | 81349-mil-i-6866 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.). |

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/4M106-08007> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.