

Description

Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	4M10612010
Minimum Qty (MOQ):	5 EA
NSN:	3120-01-273-6328
National Motor Freight:	114800, Bearing,roller,thrust

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 4M106-12010 Specifications

Overall Length:	0.5980 Inches Minimum And 0.6080 Inches Maximum
Body Outside Diameter:	0.9360 Inches Minimum And 0.9365 Inches Maximum
Body Inside Diameter:	0.7500 Inches Minimum And 0.7510 Inches Maximum
Corner Shape:	Square All Corners
Surface Finish:	63.0 Microinches Left End Surface Of Body
Surface Finish:	63.0 Microinches Outside Diameter Surface Of Body
Surface Finish:	63.0 Microinches Right End Surface Of Body
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643,cond H 1025 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	76301-4-106 Manufacturers Standard

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/4M106-12010> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.