



Military-Fasteners.com

P/N 4M106-12010

Description

Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | 4M10612010 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 3120-01-273-6328 |
| National Motor Freight: | 114800, Bearing,roller,thrust |



* See page 2 for technical characteristics

P/N 4M106-12010 Specifications

| | |
|---|--|
| Overall Length: | 0.5980 Inches Minimum And 0.6080 Inches Maximum |
| Body Outside Diameter: | 0.9360 Inches Minimum And 0.9365 Inches Maximum |
| Body Inside Diameter: | 0.7500 Inches Minimum And 0.7510 Inches Maximum |
| Corner Shape: | Square All Corners |
| Surface Finish: | 63.0 Microinches Left End Surface Of Body |
| Surface Finish: | 63.0 Microinches Outside Diameter Surface Of Body |
| Surface Finish: | 63.0 Microinches Right End Surface Of Body |
| Material: | Steel Comp 630 Overall |
| Material Document And Classification: | Ams 5643,cond H 1025 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 76301-4-106 Manufacturers Standard |

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/4M106-12010> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.