

## P/N 4M106-20001

## **Description**

Length: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 4M10620001

Minimum Qty (MOQ): 5 EA

NSN: 3120-01-132-0570

National Motor Freight: 114850, Bearing / Bushing O / T Ball / Roller I / S



<sup>\*</sup> See page 2 for technical characteristics

# P/N 4M106-20001 Specifications

Overall Length:	0.7800 Inches Minimum And 0.7850 Inches Maximum
Body Outside Diameter:	1.5604 Inches Minimum And 1.5614 Inches Maximum
Body Inside Diameter:	1.3750 Inches Minimum And 1.3760 Inches Maximum
Corner Shape:	Square All Corners
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643,cond H1025 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges

## **How to Order**

Order this bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/4M106-20001">https://military-fasteners.com/bushings/sleeve+bushings/4M106-20001</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/4M106-20001">https://military-fasteners.com/bushings/sleeve+bushings/4M106-20001</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/4M106-20001">https://military-fasteners.com/bushings/sleeve+bushings/4M106-20001</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/4M106-20001">https://military-fasteners.com/bushings/4M106-20001</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/4M106-20001">https://military-fasteners.com/bushings/4M106-20001</a> and selecting the property of the prope