

Description

Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	4M461218
Minimum Qty (MOQ):	5 EA
NSN:	3120-01-271-1808
National Motor Freight:	114800, Bearing,roller,thrust

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 4M46-12-18 Specifications

Overall Length:	0.5620 Inches Minimum And 0.5720 Inches Maximum
Body Outside Diameter:	0.8730 Inches Minimum And 0.8740 Inches Maximum
Body Inside Diameter:	0.7495 Inches Minimum And 0.7505 Inches Maximum
Corner Shape:	Square All Corners
Surface Finish:	63.0 Microinches Inside Diameter Surface Of Body
Surface Finish:	63.0 Microinches Outside Diameter Surface Of Body
Special Features:	Plating Of The Id Is Optional
Material:	Steel Comp 4130 Outer Layer Or Steel Comp 8630 Outer Layer
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Outer Layer Or Mil-s-6050 Mil Spec 2nd Material Response Outer Layer
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/4M46-12-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.