

Description

Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	4M46612
Minimum Qty (MOQ):	10 EA
NSN:	3120-00-557-4704
National Motor Freight:	114800, Bearing,roller,thrust

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 4M46-6-12 Specifications

Overall Length:	0.3750 Inches Minimum And 0.3850 Inches Maximum
Body Outside Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Body Inside Diameter:	0.3745 Inches Minimum And 0.3755 Inches Maximum
Corner Shape:	Square All Corners
Surface Finish:	63.0 Microinches Inside Diameter Surface Of Body
Surface Finish:	63.0 Microinches Outside Diameter Surface Of Body
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6798 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/4M46-6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.