

Description

Fastener Length: 5/8", Thread: 3/8-24, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	5013681
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-501-3681
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 5013681 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.271 Inches Minimum And 0.291 Inches Maximum
Fastener Length:	0.680 Inches Nominal
Head Style:	Tee No. 3
Head Height:	0.122 Inches Minimum And 0.127 Inches Maximum
Head Length:	0.697 Inches Minimum And 0.700 Inches Maximum
Width Between Flats:	0.480 Inches Minimum And 0.490 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Hardness Rating:	50.0 Rockwell D Minimum Overall And 56.0 Rockwell D Maximum Overall
Special Features:	Unthreaded Length 0.38 In. Dia
Material:	Steel Comp 4140 Overall Or Steel Comp 8640 Overall Or Steel Overall
Material Document And Classification:	Astm A-322 Assn Std 1st Material Response Overall Or Astm A-331 Assn Std 1st Material Response Overall Or Astm A-322 Assn Std 2nd Material Response Overall Or Astm A-331 Assn Std 2nd Material Response Overall Or Astm A-322 Assn Std 3rd Material Response Overall Or Astm A-331 Assn Std 3rd Material Response Overall
Surface Treatment:	Phosphate Manganese Overall Or Phosphate Zinc Overall
Surface Treatment Document And Classification:	Mil-p-16232 Type M Class 1 Mil Spec 1st Treatment Response Overall Or Mil-p-16232 Type Z Class 1 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/5013681> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.