

**Description**

Retaining Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	510040H
Minimum Qty (MOQ):	15 EA
NSN:	5325-00-804-7643
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	063520, Waveguide In Boxes / Crates



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 5100-40H Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Inside Diameter:</b>	0.361 Inches Minimum And 0.368 Inches Maximum
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Major Thickness:</b>	0.023 Inches Minimum And 0.027 Inches Maximum
<b>Ring Style:</b>	External
<b>Usage Design:</b>	External
<b>Material Hardness Rating:</b>	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
<b>Material:</b>	Steel, Ams 5520
<b>Material:</b>	Steel Comp 632
<b>Material Document And Classification:</b>	Ams 5520 Assn Std Single Material Response
<b>Surface Treatment:</b>	Passivate
<b>Surface Treatment:</b>	Passivated, Qq-p-35

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/5100-40H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.