

Description

Fastener Length: 5/8", Hole Diameter: ", Thread: 1/4-24, Head Width: 7/32", Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	56462V524H10
Minimum Qty (MOQ):	1
NSN:	5305-00-338-6085
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N 56462V524H10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Minimum And 0.640 Inches Maximum
Fastener Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.429 Inches Minimum And 0.438 Inches Maximum
Head Height:	0.306 Inches Minimum And 0.313 Inches Maximum
Hole Diameter:	0.060 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.218 Inches Minimum And 0.221 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this socket head cap screws from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/56462V524H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.