

Description

Diameter: 19/64", steel pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	5S513
Minimum Qty (MOQ):	1 EA
NSN:	5325-00-831-3400
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 5S5-13 Specifications

Grip Length:	0.276 Inches Minimum And 0.284 Inches Maximum
Diameter:	0.294 Inches Minimum And 0.306 Inches Maximum
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Fillister
Material Accommodated Thickness:	0.270 Inches Nominal
Drive Type:	Slotted
Stud Shank Major Diameter:	0.122 Inches Minimum And 0.128 Inches Maximum
Material:	Plastic Polyhexamethylene Amide Washer
Material:	Steel Comp 4037 Stud
Material:	Steel Pin
Material Document And Classification:	Astm A331 Assn Std Single Material Response Stud
Material Document And Classification:	Mil-m-20693,ty 1 Mil Spec Single Material Response Washer
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Stud And Chromate Stud
Surface Treatment:	Cadmium Pin And Chromate Pin
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Pin
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stud

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/5S5-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.