

**Description**

Diameter: 19/64", steel pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	5S513
Minimum Qty (MOQ):	1 EA
NSN:	5325-00-831-3400
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 5S5-13 Specifications

<b>Grip Length:</b>	0.276 Inches Minimum And 0.284 Inches Maximum
<b>Diameter:</b>	0.294 Inches Minimum And 0.306 Inches Maximum
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Material Accommodated Thickness:</b>	0.270 Inches Nominal
<b>Drive Type:</b>	Slotted
<b>Stud Shank Major Diameter:</b>	0.122 Inches Minimum And 0.128 Inches Maximum
<b>Material:</b>	Plastic Polyhexamethylene Amide Washer
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Pin
<b>Material Document And Classification:</b>	Astm A331 Assn Std Single Material Response Stud
<b>Material Document And Classification:</b>	Mil-m-20693,ty 1 Mil Spec Single Material Response Washer
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Pin
<b>Surface Treatment:</b>	Cadmium Stud And Chromate Stud
<b>Surface Treatment:</b>	Cadmium Pin And Chromate Pin
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Pin
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stud

## How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/5S5-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.