

Description

Diameter: 19/64", steel comp 4037 stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	5S522
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-007-8834
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 5S5-22 Specifications

Grip Length:	0.450 Inches Nominal
Diameter:	0.300 Inches Nominal
Securing Device Type:	Grommet
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Fillister
Material Accommodated Thickness:	0.335 Inches Minimum And 0.349 Inches Maximum
Drive Type:	Slotted
Stud Shank Major Diameter:	0.125 Inches Nominal
Material:	Steel Comp 4037 Stud
Material Document And Classification:	Astm A322 Assn Std Single Material Response Stud Or Astm A331 Assn Std Single Material Response Stud
Surface Treatment:	Cadmium Stud And Chromate Stud
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stud

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/5S5-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.