

**Description**

Fastener Length: 1-3/64", Thread: 10-32, Thread Length: 23/64", 6142-SS series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	6142SS10327
Minimum Qty (MOQ):	5
NSN:	5305-00-832-6777
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N 6142-SS-1032-7 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.359 Inches Minimum And 0.391 Inches Maximum
<b>Fastener Length:</b>	1.047 Inches Minimum And 1.078 Inches Maximum
<b>Head Style:</b>	Knurled No. 1
<b>Head Diameter:</b>	0.433 Inches Minimum And 0.443 Inches Maximum
<b>Head Height:</b>	0.234 Inches Minimum And 0.266 Inches Maximum
<b>First Diameter From Head:</b>	0.125 Inches Minimum And 0.135 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	0.678 Inches Minimum And 0.698 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Externally Relieved Body Diameter Quantity:</b>	1
<b>Special Features:</b>	Cone Point 82 Deg
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-f-14072 Finish No. E300 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/6142-SS-1032-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.