

Description

Fastener Length: 1-3/64", Thread: 10-32, Thread Length: 23/64", 6142-SS series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	6142SS10327
Minimum Qty (MOQ):	5
NSN:	5305-00-832-6777
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 6142-SS-1032-7 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.359 Inches Minimum And 0.391 Inches Maximum
Fastener Length:	1.047 Inches Minimum And 1.078 Inches Maximum
Head Style:	Knurled No. 1
Head Diameter:	0.433 Inches Minimum And 0.443 Inches Maximum
Head Height:	0.234 Inches Minimum And 0.266 Inches Maximum
First Diameter From Head:	0.125 Inches Minimum And 0.135 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.678 Inches Minimum And 0.698 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Externally Relieved Body Diameter Quantity:	1
Special Features:	Cone Point 82 Deg
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072 Finish No. E300 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/6142-SS-1032-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.