

Description

Thread Size: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	6274CSS10327
Minimum Qty (MOQ):	5
NSN:	5325-01-163-6205
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N 6274C-SS-1032-7 Specifications

Thread Class:	2b
Flange Diameter:	0.528 Inches Minimum And 0.534 Inches Maximum
Flange Thickness:	0.432 Inches Minimum And 0.442 Inches Maximum
Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Insert Size:	0.430 In. Min And 0.433 In. Max Insert Size
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	Counterbore In Shank 0.374 In. Min And 0.377 In. Max Dia To 0.427 In. Minand 0.442 In. Max Dp
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/6274C-SS-1032-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.