

**Description**

Thread Size: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	6274CSS10327
Minimum Qty (MOQ):	5
NSN:	5325-01-163-6205
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 6274C-SS-1032-7 Specifications

<b>Thread Class:</b>	2b
<b>Flange Diameter:</b>	0.528 Inches Minimum And 0.534 Inches Maximum
<b>Flange Thickness:</b>	0.432 Inches Minimum And 0.442 Inches Maximum
<b>Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Insert Size:</b>	0.430 In. Min And 0.433 In. Max Insert Size
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Special Features:</b>	Counterbore In Shank 0.374 In. Min And 0.377 In. Max Dia To 0.427 In. Minand 0.442 In. Max Dp
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/6274C-SS-1032-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.