

Description

Fastener Length: 45/64", Thread: 1/4-28, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	6310206
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-873-7164
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 63-10206 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Minimum And 0.260 Inches Maximum
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.495 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	28.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Comp 4130
Screw Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/63-10206> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.