

**Description**

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	642AS75221
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-080-5719
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 642AS7522-1 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.169 Inches Minimum And 0.250 Inches Maximum
<b>Fastener Length:</b>	0.219 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.183 Inches Nominal
<b>Head Height:</b>	0.107 Inches Nominal
<b>Locking Feature:</b>	Strip Threads
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Material:</b>	Plastic Locking Feature
<b>Material:</b>	Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 304 Fastener
<b>Material Document And Classification:</b>	Qq-s-763 Cond B Fed Spec 1st Material Response Overall Or Qq-s-763 Cond B Fed Spec 2nd Material Response Overall Or Astm A582 Assn Std 3rd Material Response Overall
<b>Surface Treatment:</b>	Passivate Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/642AS7522-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.